



www.futrol.com

TECHNICAL DATA SHEET

Grade : SAE 0w30 API SM/CF

Name : TUNDRA Semi Synthetic Grade

PRODUCT DESCRIPTION : TUNDRA 0w30 is premium grade engine oil especially developed and formulated with the finest synthetic base stocks and advanced additive technology, to keep engines healthy and efficient. It reduces carbon sludge build up under harsh driving conditions. It provides superior low friction with strengthened oil film for greater engine response and fuel efficiency. It fulfils or exceeds the service requirements of API SM/CF and it is excellently suitable for use in passenger cars driven on petrol and diesel fuel.

PERFORMANCE BENEFITS: -

- Excellent high heat & wear protection.
- Excellent viscosity retention.
- Excellent engine protection under harsh driving conditions
- Long drain intervals.
- Reduce carbon sludge build up.
- Low fuel and oil consumptions.
- Excellent low temperature characteristics.
- Superior low friction properties.

Applications: TUNDRA 0w30 is recommended for use in petrol, diesel vehicles, where service requiring of API SM/CF, SN Plus, SN, ACEA A3/B4. Always check your owner's manual for the recommended viscosity grades & specifications of your particular cars/vans.

TYPICAL CHARACTERISTICS:

| Sr. No. | PARAMETER | TEST METHOD | VALUE |
|---------|--------------------------------|-------------|-------|
| 1 | Kinematic viscosity, cst@100°C | ASTM D 445 | 12.5 |
| 2 | Viscosity index | ASTM D 2270 | 180 |
| 3 | Flash point, COC, deg °C | ASTM D 92 | 200 |
| 4 | Pour point deg° C | ASTM D 97 | -45 |
| 5 | TBN mg KOH/mg | ASTM D 2896 | 9.0 |

For more information about this product and other products in our range please scan the following:

For Queries & Feedback:
1800 12322 07 (Toll Free)

WEBSITE
www.futrol.com

EMAIL SALES
info@furyoils.com

EMAIL TECHNICAL SUPPORT
cm@furyoils.com