



www.futrol.com

TECHNICAL DATA SHEET

Grade : SAE 10w30 API: SN (JASO/MA2)

Name : ACTIVE PLUS – SYNTHETIC GRADE

PRODUCT DESCRIPTION: **ACTIVE PLUS 10w-30** is a SYNTHETIC quality engine oil developed for 4 Stroke motorcycle engines. It is designed to perform maximum power under high RPM, reduces internal losses. Its unique formulation provides proper engine cleaning protects against new sludge formation and extended life your engine better engine efficiency and protection against wear and corrosion.

PERFORMANCE BENEFITS: -

- ✓ Excellent cleaning due to its effective detergency and dispersancy properties
- ✓ Excellent anti wear property
- ✓ Reduces thermal and oxidation deposits
- ✓ Its anti-frictional properties reductions vibration and noise
- ✓ Smoother clutch operation
- ✓ Longer service life

APPLICATIONS: **ACTIVE PLUS** 10W-30 is designed to optimise performance and protection for modern motorcycles where API SN and JASO MA2 are recommended.

TYPICAL CHARACTERISTICS:-

S.N.	PARAMETER	TEST METHOD	VALUE
1	Appearance	VISUAL	Bright & Clear
2	Kinematic Viscosity, cSt@100°C	ASTM D 445	10.5
3	Viscosity Index	ASTM D 2270	150
4	Flash Point, COC, deg °C	ASTM D 92	240
5	Pour Point deg° C	ASTM D 97	-45
6	TBN mg KOH/mg	ASTM D 2896	6.00

For more information about this product and other products in our range please scan the following:

For Queries & Feedback:
1800 12322 07 (Toll Free)

WEBSITE
www.futrol.com

EMAIL SALES
info@furyoils.com

EMAIL TECHNICAL SUPPORT
cm@furyoils.com



www.futrol.com

TECHNICAL DATA SHEET

Grade : SAE 10w30 API: SM (JASO/MA2)

Name : ACTION PRO (SEMI SYNTHETIC GRADE)

PRODUCT DESCRIPTION : **ACTION PRO 10w-30** advanced premium quality engine oil developed for 4Stroke motorcycle engines. It is designed to perform maximum power under high RPM, reduces internal loses. Its unique formulation provides proper engine cleaning protects against new sludge formation and extended life your engine better engine efficiency and protection against wear and corrosion.

PERFORMANCE BENEFITS: -

- ✓ Excellent cleaning due to its effective detergency and dispersancy properties
- ✓ Excellent anti wear property
- ✓ Reduces thermal and oxidation deposits
- ✓ Its anti-frictional properties reductions vibration and noise
- ✓ Smoother clutch operation
- ✓ Longer service life

APPLICATIONS: **ACTION PRO 10W-30** is designed to optimise performance and protection for modern motorcycles where API SM and JASO MA2 are recommended.

TYPICAL CHARACTERSTICS:-

S.N.	PARAMETER	TEST METHOD	VALUE
1	Appearance	VISUAL	Bright & Clear
2	Kinematic Viscosity, cSt@100°C	ASTM D 445	10.5
3	Viscosity Index	ASTM D 2270	150
4	Flash Point, COC, deg °C	ASTM D 92	209
5	Pour Point deg° C	ASTM D 97	-21
6	TBN mg KOH/mg	ASTM D 2896	6.00

For more information about this product and other products in our range please scan the following:

For Queries & Feedback:
1800 12322 07 (Toll Free)

WEBSITE
www.futrol.com

EMAIL SALES
info@furyoils.com

EMAIL TECHNICAL SUPPORT
cmi@furyoils.com



www.futrol.com

TECHNICAL DATA SHEET

Grade : SAE 10w30 API: SL (JASO/MA2)

Name : MAGIC PLUS MINERAL GRADE

PRODUCT DESCRIPTION : **MAGIC PLUS 10w-30** advanced premium quality engine oil developed for 4 Stroke motorcycle engines. It is designed to perform maximum power under high RPM, reduces internal loses. Its unique formulation provides proper engine cleaning protects against new sludge formation and extended life your engine better engine efficiency and protection against wear and corrosion.

PERFORMANCE BENEFITS: -

- ✓ Excellent cleaning due to its effective detergency and dispersancy properties
- ✓ Excellent anti wear property
- ✓ Reduces thermal and oxidation deposits
- ✓ Its anti-frictional properties reductions vibration and noise
- ✓ Smoother clutch operation
- ✓ Longer service life

APPLICATIONS: **MAGIC PLUS 10W-30** is designed to optimise performance and protection for modern motorcycles where API SL and JASO MA2 are recommended.

TYPICAL CHARACTERSTICS:-

S.N.	PARAMETER	TEST METHOD	VALUE
1	Appearance	VISUAL	Bright & Clear
2	Kinematic Viscosity, cSt@100°C	ASTM D 445	10.5
3	Viscosity Index	ASTM D 2270	150
4	Flash Point, COC, deg °C	ASTM D 92	209
5	Pour Point deg° C	ASTM D 97	-21
6	TBN mg KOH/mg	ASTM D 2896	6.00

For more information about this product and other products in our range please scan the following:

For Queries & Feedback:
1800 12322 07 (Toll Free)

WEBSITE
www.futrol.com

EMAIL SALES
info@furyoils.com

EMAIL TECHNICAL SUPPORT
cmi@furyoils.com