



www.futrol.com

TECHNICAL DATA SHEET

Grade : SAE 0w-16/20 API SL/CF
Name : Super Atlantic – Semi Synthetic

PRODUCT DESCRIPTION: Super Atlantic SAE 0w-16/20 API SL Motor Oil is a low-viscosity fuel saving semi synthetic oils combined with premium quality additives. SAE 0W-16 low viscosity grade of motor oil suitable late model cars (use the viscosity grade the owner's manual recommends). Super Atlantic SAE 0W-16 Motor Oil is for long life and great fuel economy. Super Atlantic oil is blended with low friction & long lasting fuel saving technology,

PERFORMANCE BENEFITS: -

- Excellent high heat & wear protection.
- Excellent viscosity retention.
- Excellent engine protection under harsh driving conditions
- Long drain intervals.
- Reduce carbon sludge build up.
- Low fuel and oil consumptions.
- Excellent low temperature characteristics.
- Superior low friction properties.

Applications: Super Atlantic 0w-16 is recommended for late model cars for all driving conditions use in petrol/CNG vehicles, where service requiring of API SL/CF, SN Plus, SN, ILSAC GF-B6. Always check your owner's manual for the recommended viscosity grades & specifications of your particular cars/vans.

TYPICAL CHARACTERISTICS:

Sr. No.	PARAMETER	TEST METHOD	VALUE
1	Kinematic viscosity, cst@100°C	ASTM D 445	12.5
2	Viscosity index	ASTM D 2270	180
3	Flash point, COC, deg °C	ASTM D 92	200
4	Pour point deg° C	ASTM D 97	-45
5	TBN mg KOH/mg	ASTM D 2896	9.0

For more information about this product and other products in our range please scan the following:

For Queries & Feedback:
1800 12322 07 (Toll Free)

WEBSITE
www.futrol.com

EMAIL SALES
info@furyoils.com

EMAIL TECHNICAL SUPPORT
cm@furyoils.com