



www.futrol.com

TECHNICAL DATA SHEET

Grade : SAE 40 / CF (Diesel Engine Oil)

Name : ULTRA SUPER

PRODUCT DESCRIPTION: ULTRA SUPER SAE-40 is a premium mono grade diesel engine oil formulated with highly refined base stocks and other performance proven additives to enrich the performance with properties like oxidation stability, high viscosity index, excellent anti-wear and corrosion protection to engine components.

PERFORMANCE BENEFITS: -

- ✓ Longer drain period
- ✓ Excellent wear protection
- ✓ Reduces oil consumption
- ✓ Does not allow harmful deposits on vital engine parts through reduced sludge formation
- ✓ Keeps engine clean due to its effective detergency and dispersancy properties

APPLICATIONS:- ULTRA SUPER, SAE-10 is recommended for use in naturally aspirated or turbo charged diesel engine of heavy-duty vehicles, tractors, trucks, and LCV's

TYPICAL CHARACTERISTICS:-

S.N	PARAMETER	TEST METHOD	VALUE
1	Appearance	VISUAL	Bright & clear
2	Kinematic viscosity, cSt@100°C	ASTM D 445	14.00
3	Viscosity index	ASTM D 2270	110
4	Flash point, COC, deg °C	ASTM D 92	220
5	Pour point deg° C	ASTM D 97	-24
6	TBN mg KOH/mg	ASTM D 2896	8.00

For more information about this product and other products in our range please scan the following:

For Queries & Feedback:
1800 12322 07 (Toll Free)

WEBSITE
www.futrol.com

EMAIL SALES
info@furyoils.com

EMAIL TECHNICAL SUPPORT
cm@furyoils.com