



Futrol Petrochem ENGINE OILS | GEAR OILS | GREASES

TECHNICAL DATA SHEET

SAE 50 / CF (Diesel Engine Oil) Grade

Name **ULTRA HD**

PRODUCT DESCRIPTION: ULTRA HD SAE-50 is a premium mono grade diesel engine oil formulated with highly refined base stocks and other performance proven additives to enrich the performance with properties like oxidation stability, high viscosity index, excellent antiwear and corrosion protection to engine components.

PERFORMANCE BENEFITS: -

- ✓ Longer drain period
- ✓ Excellent wear protection
- ✓ Reduces oil consumption
- ✓ Does not allow harmful deposits on vital engine parts through reduced sludge formation
- ✓ Keeps engine clean due to its effective detergency and dispersancy properties

APPLICATIONS:- ULTRA HD, SAE-50 is recommended for use in naturally aspirated or turbo charged diesel engine of heavy-duty vehicles, tractors, trucks, and LCV's

TYPICAL CHARACTERISTICS:-

YPIC	AL CHARACTERISTICS:-		
S.N	PARAMETER	TEST METHOD	VALUE
1	Appearance	VISUAL	Bright & clear
2	Kinematic viscosity, cSt@100°C	ASTM D 445	15.50
3	Viscosity index	ASTM D 2270	115
4	Flash point, COC, deg °C	ASTM D 92	220
5	Pour point deg° C	ASTM D 97	-24
6	TBN mg KOH/mg	ASTM D 2896	8.50

For more information about this product and other products in our range please scan the following:

For Queries & Feedback: 1800 12322 07 (Toll Free)

WEBSITE www.futrol.com **EMAIL SALES** info@furyoils.com EMAIL TECHNICAL SUPPORT cm@furyoils.com