



www.futrol.com

TECHNICAL DATA SHEET

Grade : SAE 15w-40 - API CK4/SN

Name : SUPERSONIC

PRODUCT DESCRIPTION: SUPERSONIC 15w-40 CK4/SN is premium quality heavy duty diesel engine oil specially designed for low emission for late model vehicles. It is also recommended for a wide range of diesel engines required the latest API –CK4 performance lubricants operating under the most severe service conditions. Its mixed fleet motor oil recommended for naturally aspirated & turbo charged diesel engines in which CK4 grade is recommended off-high ways & construction applications.

PERFORMANCE BENEFITS: -

- ✓ Outstanding wear protection & performance
- ✓ Maximum engine Life, Keeps engine clean.
- ✓ High reserve alkalinity provides excellent corrosion protection and longer service life
- ✓ High shear stability maintains needed oil viscosity at higher temperature

APPLICATIONS: - SUPERSONIC CK4 is mixed fleets motor oil, highly recommended for use in naturally aspirated or turbo charged diesel engines of heavy duty commercial or passenger vehicles and off-high ways equipments where 15w40 CK4 type of lubricant is required

TYPICAL CHARACTERISTICS:-

S.N	PARAMETER	TEST METHOD	VALUE
1	Appearance	Visual	Bright & Clear
2	Kinematic Viscosity, cSt@100°C	ASTM D 445	15.00
3	Viscosity index	ASTM D 2270	135
4	Flash point, COC, deg °C	ASTM D 92	236
5	Pour point deg° C	ASTM D 97	-36
6	TBN mg KOH/mg	ASTM D 2896	9.5

For more information about this product and other products in our range please scan the following:

For Queries & Feedback:
1800 12322 07 (Toll Free)

WEBSITE
www.futrol.com

EMAIL SALES
info@furyoils.com

EMAIL TECHNICAL SUPPORT
cm@furyoils.com