



www.futrol.com

## TECHNICAL DATA SHEET

**Grade : SAE 10w40 API: SL (JASO/MA2)**

**Name : 4T Magnum (Multi Grade)**

**PRODUCT DESCRIPTION:** 4T Magnum 10w40 is premium quality multigrade 4 Stroke engine oil formulated with highest quality base stocks & performance based additives for ultimate protection/performance operating under all weather conditions, Wet clutch compatible and recommended for Japanese and other motorcycles where API SL or JASO MA. Optimized for lubrications systems where engine, gear box & clutch are integrated.

### **PERFORMANCE BENEFITS: -**

- ✓ Excellent cleaning due to its effective detergency and dispersancy properties
- ✓ Excellent anti wear property
- ✓ Reduces thermal and oxidation deposits
- ✓ Its anti-frictional properties reductions vibration and noise
- ✓ Smoother clutch operation
- ✓ Longer service life

**APPLICATIONS:** 4T Magnum 10W-40 is designed to optimise performance and protection for modern motorcycles where API SL and JASO MA are recommended.

### **TYPICAL CHARACTERSTICS:-**

S.N.	PARAMETER	TEST METHOD	VALUE
1	Appearance	VISUAL	Bright & Clear
2	Kinematic Viscosity, cSt@100°C	ASTM D 445	14.5
3	Viscosity Index	ASTM D 2270	160
4	Flash Point, COC, deg °C	ASTM D 92	217
5	Pour Point deg° C	ASTM D 97	-36
6	TBN mg KOH/mg	ASTM D 2896	7.5

For more information about this product and other products in our range please scan the following:

**For Queries & Feedback:**  
1800 12322 07 (Toll Free)

WEBSITE  
[www.futrol.com](http://www.futrol.com)

EMAIL SALES  
[info@furyoils.com](mailto:info@furyoils.com)

EMAIL TECHNICAL SUPPORT  
[cmi@furyoils.com](mailto:cmi@furyoils.com)



www.futrol.com

## TECHNICAL DATA SHEET

**Grade : SAE 10w40 API: SM (JASO/MA2)**

**Name : 4T Magnum Plus (Semi Synthetic)**

**PRODUCT DESCRIPTION:** 4T Magnum Plus 10w40 is Premium Quality semi synthetic 4 Stroke engine oil formulated with highest quality base stocks & performance based additives for ultimate protection/performance operating under all weather conditions, Wet clutch compatible and recommended for Japanese and other motorcycles where API SM or JASO MA. Optimized for lubrications systems where engine, gear box & clutch are integrated.

### **PERFORMANCE BENEFITS: -**

- ✓ Excellent cleaning due to its effective detergency and dispersancy properties
- ✓ Excellent anti wear property
- ✓ Reduces thermal and oxidation deposits
- ✓ Its anti-frictional properties reductions vibration and noise
- ✓ Smoother clutch operation
- ✓ Longer service life

**APPLICATIONS:** 4T Magnum Plus 10W-40 is designed to optimise performance and protection for modern motorcycles where API SM and JASO MA are recommended.

### **TYPICAL CHARACTERSTICS:-**

S.N.	PARAMETER	TEST METHOD	VALUE
1	Appearance	VISUAL	Bright & Clear
2	Kinematic Viscosity, cSt@100°C	ASTM D 445	14.5
3	Viscosity Index	ASTM D 2270	160
4	Flash Point, COC, deg °C	ASTM D 92	217
5	Pour Point deg° C	ASTM D 97	-36
6	TBN mg KOH/mg	ASTM D 2896	7.5

For more information about this product and other products in our range please scan the following:

**For Queries & Feedback:**  
1800 12322 07 (Toll Free)

WEBSITE  
[www.futrol.com](http://www.futrol.com)

EMAIL SALES  
[info@furyoils.com](mailto:info@furyoils.com)

EMAIL TECHNICAL SUPPORT  
[cmi@furyoils.com](mailto:cmi@furyoils.com)



www.futrol.com

## TECHNICAL DATA SHEET

**Grade : SAE 10w40 API: SM (JASO/MA2)**

**Name : 4T Magnum Ultra Synthetic Grade**

**PRODUCT DESCRIPTION :** 4T Magnum Ultra 10w40 is Synthetic grade 4 Stroke engine oil formulated with highest quality base stocks & performance based additives for ultimate protection/performance operating under all weather conditions, Wet clutch compatible and recommended for Japanese and other motorcycles where API SN or JASO MA, Optimized for lubrications systems where engine, gear box & clutch are integrated.

### **PERFORMANCE BENEFITS: -**

- ✓ Excellent cleaning due to its effective detergency and dispersancy properties
- ✓ Excellent anti wear property
- ✓ Reduces thermal and oxidation deposits
- ✓ Its anti-frictional properties reductions vibration and noise
- ✓ Smoother clutch operation
- ✓ Longer service life

**APPLICATIONS:** 4T Mega Plus 10W-40 is designed to optimise performance and protection for modern motorcycles where API SN and JASO MA are recommended.

### **TYPICAL CHARACTERISTICS:-**

S.N.	PARAMETER	TEST METHOD	VALUE
1	Appearance	VISUAL	Bright & Clear
2	Kinematic Viscosity, cSt@100°C	ASTM D 445	14.5
3	Viscosity Index	ASTM D 2270	160
4	Flash Point, COC, deg °C	ASTM D 92	217
5	Pour Point deg° C	ASTM D 97	-36
6	TBN mg KOH/mg	ASTM D 2896	7.5

For more information about this product and other products in our range please scan the following:

**For Queries & Feedback:**  
1800 12322 07 (Toll Free)

WEBSITE  
[www.futrol.com](http://www.futrol.com)

EMAIL SALES  
[info@furyoils.com](mailto:info@furyoils.com)

EMAIL TECHNICAL SUPPORT  
[cmi@furyoils.com](mailto:cmi@furyoils.com)