



www.futrol.com

## TECHNICAL DATA SHEET

**Grade : SAE 10w50 API: SL (JASO/MA2)**

**Name : 4T Ultima (Multi Grade)**

**PRODUCT DESCRIPTION:** 4T Ultima 10w50 is premium quality multi grade high performance 4 Stroke engine oil formulated from high quality base stocks & added with performance based additives for ultimate protection /performance operating under all weather conditions, wet clutch compatible and recommended for Japanese and other motorcycles where API SL or JASO MA.

### **PERFORMANCE BENEFITS: -**

- ✓ Excellent cleaning due to its effective detergency and dispersancy properties
- ✓ Excellent anti wear property
- ✓ Reduces thermal and oxidation deposits
- ✓ Its anti-frictional properties reductions vibration and noise
- ✓ Smoother clutch operation
- ✓ Longer service life

**APPLICATIONS:** 4T Ultima 10W-50 is designed to optimise performance and protection for modern motorcycles where API SL and JASO MA are recommended.

### **TYPICAL CHARACTERSTICS:-**

S.N.	PARAMETER	TEST METHOD	VALUE
1	Appearance	VISUAL	Bright & Clear
2	Kinematic Viscosity, cSt@100°C	ASTM D 445	17
3	Viscosity Index	ASTM D 2270	168
4	Flash Point, COC, deg °C	ASTM D 92	217
5	Pour Point deg° C	ASTM D 97	-33
6	TBN mg KOH/mg	ASTM D 2896	9.8

For more information about this product and other products in our range please scan the following:

**For Queries & Feedback:**  
1800 12322 07 (Toll Free)

WEBSITE  
[www.futrol.com](http://www.futrol.com)

EMAIL SALES  
[info@furyoils.com](mailto:info@furyoils.com)

EMAIL TECHNICAL SUPPORT  
[cmi@furyoils.com](mailto:cmi@furyoils.com)



www.futrol.com

## TECHNICAL DATA SHEET

**Grade : SAE 10w50 API: SM (JASO/MA2)**

**Name : 4T Ultima Pro (Semi Synthetic Grade)**

**PRODUCT DESCRIPTION:** 4T Ultima Pro 10w50 is premium quality semi synthetic grade - high performance 4 Stroke engine oil formulated from high quality base stocks & blended with performance based additives for ultimate protection /performance operating under all weather conditions, wet clutch compatible and recommended for Japanese and other motorcycles where API SM or JASO MA.

### **PERFORMANCE BENEFITS: -**

- ✓ Excellent cleaning due to its effective detergency and dispersancy properties
- ✓ Excellent anti wear property
- ✓ Reduces thermal and oxidation deposits
- ✓ Its anti-frictional properties reductions vibration and noise
- ✓ Smoother clutch operation
- ✓ Longer service life

**APPLICATIONS:** 4T Ultima Pro 10W-50 is designed to optimise performance and protection for modern motorcycles where API SL and JASO MA are recommended.

### **TYPICAL CHARACTERSTICS:-**

S.N.	PARAMETER	TEST METHOD	VALUE
1	Appearance	VISUAL	Bright & Clear
2	Kinematic Viscosity, cSt@100°C	ASTM D 445	17
3	Viscosity Index	ASTM D 2270	168
4	Flash Point, COC, deg °C	ASTM D 92	217
5	Pour Point deg° C	ASTM D 97	-33
6	TBN mg KOH/mg	ASTM D 2896	9.8

For more information about this product and other products in our range please scan the following:

**For Queries & Feedback:**  
1800 12322 07 (Toll Free)

WEBSITE  
[www.futrol.com](http://www.futrol.com)

EMAIL SALES  
[info@furyoils.com](mailto:info@furyoils.com)

EMAIL TECHNICAL SUPPORT  
[cmi@furyoils.com](mailto:cmi@furyoils.com)



www.futrol.com

## TECHNICAL DATA SHEET

**Grade : SAE 10w50 API: SN (JASO/MA2)**

**Name : 4T Ultima Plus (Synthetic Grade)**

**PRODUCT DESCRIPTION :** 4T Ultima Plus 10w50 is premium quality synthetic grade performance 4 Stroke engine oil formulated from high quality base stocks & added with performance based additives for ultimate protection/performance operating under all weather conditions, wet clutch compatible and recommended for Japanese and other motorcycles where API SN or JASO MA/MA2 .

### **PERFORMANCE BENEFITS: -**

- ✓ Excellent cleaning due to its effective detergency and dispersancy properties
- ✓ Excellent anti wear property
- ✓ Reduces thermal and oxidation deposits
- ✓ Its anti-frictional properties reductions vibration and noise
- ✓ Smoother clutch operation
- ✓ Longer service life

**APPLICATIONS:** 4T Ultima Plus 10W-50 is designed for high performance 4-stroke sports bikes to deliver optimum power & protection in all conditions. Suitable for bikes both carburettor and fuel injected where API SN & JASO MA/MA2 specs were recommended.

### **TYPICAL CHARACTERSTICS:-**

S.N.	PARAMETER	TEST METHOD	VALUE
1	Appearance	VISUAL	Bright & Clear
2	Kinematic Viscosity, cSt@100°C	ASTM D 445	17
3	Viscosity Index	ASTM D 2270	168
4	Flash Point, COC, deg °C	ASTM D 92	217
5	Pour Point deg° C	ASTM D 97	-35
6	TBN mg KOH/mg	ASTM D 2896	9.8

For more information about this product and other products in our range please scan the following:

**For Queries & Feedback:**  
1800 12322 07 (Toll Free)

WEBSITE  
[www.futrol.com](http://www.futrol.com)

EMAIL SALES  
[info@furyoils.com](mailto:info@furyoils.com)

EMAIL TECHNICAL SUPPORT  
[cmi@furyoils.com](mailto:cmi@furyoils.com)