



www.futrol.com

TECHNICAL DATA SHEET

Grade : SAE 15w-40 API CI4+/SL
Name : TURBO PLUS

PRODUCT DESCRIPTION: -

FUTROL - Turbo Plus 15w-40 CI4+ /SL is excellent diesel engine lubricant designed for naturally aspirated or turbocharged engine. It is formulated from highly refined based stocks and performance proven additives to provide excellent anti wear, high reserve Alkalinity, engine components protection, excellent shear stability etc. It is designed to result in reduced fuel consumption and prolonged drain interval

PERFORMANCE BENEFITS: -

- ✓ Excellent anti wear Engine Life
- ✓ High reserve alkalinity provides excellent corrosion protection and longer service life
- ✓ Keeps engine clean
- ✓ High shear stability maintains needed oil viscosity at higher temperature
- ✓ Smooth engine performance

APPLICATIONS: - Turbo Plus 15w40 CI4+ is highly recommended for use in naturally aspirated or turbo charged diesel engines of Heavy Duty Commercial or Passenger vehicles and Off Road equipments where 15w40 type of lubricant is required

TYPICAL CHARACTERISTICS:-

S.N.	PARAMETER	TEST METHOD	VALUE
1	Appearance	Visual	Bright & Clear
2	Kinematic Viscosity, cSt@100°C	ASTM D 445	15.00
3	Viscosity Index	ASTM D 2270	135
4	Flash point, COC, deg °C	ASTM D 92	236
5	Pour Point Deg° C	ASTM D 97	-30
6	TBN mg KOH/mg	ASTM D 2896	11.8

For more information about this product and other products in our range please scan the following:

For Queries & Feedback:
1800 12322 07 (Toll Free)

WEBSITE
www.futrol.com

EMAIL SALES
info@furyoils.com

EMAIL TECHNICAL SUPPORT
cmi@furyoils.com