



www.futrol.com

## TECHNICAL DATA SHEET

**Grade : SAE 20w-40 API : SL/CF**

**Name : PREMIUM – MULTI**

**PRODUCT DESCRIPTION:- PREMIUM Multi - 20W-40** is high quality multigrade diesel engine oil blended with superior quality high viscosity index base oil with required additives to provide high detergency, dispersancy and anti-oxidation characteristics. It is formulated to perform under the most stringent operating conditions of heavy duty diesel engines. It offers outstanding protection against oil degradation, oil thickening and corrosion, good shear stability and maintains its viscosity under high shear, high temperature conditions. 20W-40 gives highest level of protection for relatively older diesel engines, large or small, non-turbocharged or turbocharged diesel engines

### PERFORMANCE BENEFITS: -

- ✓ Excellent wear protection
- ✓ Resistance to Oxidation and Thermal Degradation
- ✓ Enhanced Engine Life.
- ✓ Engine Cleanliness
- ✓ Good TBN Retention
- ✓ Improved mileage & reduced operational cost.

**APPLICATIONS:- PREMIUM Multi 20w-40** is recommended for use in relatively older diesel engines, large or small, non-turbocharged or turbocharged diesel engines.

### TYPICAL CHARACTERSTICS:-

S.N.	PARAMETER	TEST METHOD	VALUE
1	Appearance	VISUAL	Bright and clear
2	Kinematic Viscosity, cSt@100°C	ASTM D 445	14.5
3	Viscosity Index	ASTM D 2270	120
4	Flash Point, COC, deg °C	ASTM D 92	236
5	Pour point deg° C	ASTM D 97	-21
6	TBN mg KOH/mg	ASTM D 2896	8.5

For more information about this product and other products in our range please scan the following:

**For Queries & Feedback:**  
1800 12322 07 (Toll Free)

WEBSITE  
[www.futrol.com](http://www.futrol.com)

EMAIL SALES  
[info@furyoils.com](mailto:info@furyoils.com)

EMAIL TECHNICAL SUPPORT  
[cmi@furyoils.com](mailto:cmi@furyoils.com)